

# SAFETY DATA SHEET

1. Identification	
Product identifier	Obtura Cleaning Solution
Other means of identification	
Part Number	822-609, 3069-01A, 823-703, 823-803
Recommended use	A solvent degreasing agent designed for removing tar, adhesives, grease, oil and other residues from metal and other hard surfaces.
Recommended restrictions	None known.

#### Manufacturer/Importer/Supplier/Distributor information

Manufactured for: Company name Address	Obtura Spartan 2260 Wendt St. Algonquin, IL 60102 1-800-344-1321
In Case of Emergency	Infotrac: 24-Hour Number - (U.S.)1-800-535-5053 Outside U.S1-352-323-3500

## 2. Hazard(s) identification

Label elements

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Sensitization, skin	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	



	$\bullet$ $\bullet$ $\bullet$
Signal word	Danger
Hazard statement	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wear eye/face protection. Avoid breathing gas. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves.
Response	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Specific treatment (see this label). If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Storage	Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Not applicable.

## 3. Composition/information on ingredients

Chemical name	Common name and synonyms	CAS number	%
Distillates Petroleum Hydrotreat Light	ed	64742-47-8	60 - 70
3-Methoxy-3-methyl-1-butanol (MMB)		56539-66-3	10 - 20
d-limonene		5989-27-5	10 - 20
Carbon Dioxide		124-38-9	1 - 3
4. First-aid measures			
Inhalation	Remove victim to fresh air and keep at rest in a p artificial respiration if needed. Do not use mouth- Induce artificial respiration with the aid of a pock proper respiratory medical device. Call a POISO	to-mouth method if victin et mask equipped with a	n inhaled the substand one-way valve or othe
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists.		
Eye contact	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lens Get medical attention if irritation develops and persists.		
Ingestion	Call a physician or poison control center immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.		
Most important symptoms/effects, acute and delayed	Irritant effects. Symptoms may include stinging, t Defatting of the skin. Rash. Symptoms of overex drowsiness, headaches, confusion, decreased c are reversible if exposure is stopped.	posure can include short	ness of breath,
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat s give oxygen. Keep victim under observation. Syr		of shortness of breath
General information	In the case of accident or if you feel unwell, seek where possible). Ensure that medical personnel precautions to protect themselves.		
5. Fire-fighting measures			
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical	powder. Carbon dioxide	(CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this v	vill spread the fire.	
Specific hazards arising from the chemical	Contents under pressure. Pressurized container	may explode when expo	sed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipn face shield, gloves, rubber boots, and in enclose clothing will only provide limited protection.		
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fur consider the hazards of other involved materials, without risk. Water runoff can cause environment	Move containers from fi	
Specific methods	Use standard firefighting procedures and consider container from fire area if it can be done without breathe fumes.		
General fire hazards	Extremely flammable aerosol.		

## 6. Accidental release measures

Personal precautions,	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of
protective equipment and	low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area).
emergency procedures	Wear appropriate personal protective equipment. Do not touch damaged containers or spilled
<b>U</b>	material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists.
	Ventilate closed spaces before entering them. Local authorities should be advised if significant
	spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapors or divert vapor cloud drift. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling Conditions for safe storage,	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains. Level 3 Aerosol.
including any incompatibilities	Contents under pressure. Keep away from heat, sparks and open flame. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

## 8. Exposure controls/personal protection

#### **Occupational exposure limits**

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3
		5000 ppm
US. ACGIH Threshold Lir	nit Values	
Components	Туре	Value
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
US. NIOSH: Pocket Guide	e to Chemical Hazards	
Components	Туре	Value
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3
,		30000 ppm
	TWA	9000 mg/m3
		5000 ppm
logical limit values	No biological exposure limits noted for the ingredient(s).	
propriate engineering trols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
vidual protection measur	es, such as personal protective equipn	nent

Eye/face protection	Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.
Skin protection	
Hand protection	Chemical resistant gloves are recommended.

Other	Avoid contact with clothing. Wear suitable protective clothing. Chemical resistant gloves.
Respiratory protection	No personal respiratory protective equipment normally required. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.
Thermal hazards	Not applicable.
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

Physical stateGas.FormAerosol.ColorClear, Off-white.OdorOrangeOdor thresholdNot establishedpHNot establishedInitial point/freezing pointNot establishedInitial point and boiling302 °F (> 150 °C)arange> 01. BuAcFlash point> 01. BuAcIpper/lower flasmability or subished> 01. BuAcIpper/lower flasmability or subished> 01. BuAcflasmability foolid, gasNot available.Ipper/lower flasmability or subished> 0.7 %flasmability limit - lower% Not available.ispoire flasmability intial- lower (%)Not available.Vapor density> 01 (air = 1)Relative densityNot available.Solubility (water)< 15 %Partition coefficient> 01 established(n-o-ctanol/water)> 01 establishedViscosity> 03 sQ °F (> 200 °C)Viscosity> 03 established(n-o-ternol/water)> 01 establishedPartition coefficient> 01 establishedViscosity> 03 establishedParent volatility> 03 establishedParent volatility> 03 establishedParent volatility> 03 establishedParent volatility> 03 establishedPartition coefficient> 03 establishedPartition coefficient> 03 establishedPartition coefficient> 03 establishedParent volatility> 03 establishedParent volatility> 03 esta	Appearance	
ColorClear, Off-white.OdorOrangeOdor thresholdNot establishedpHNot apilcableMelting point/freezing pointNot establishedInitial boiling point and boiling>302 °F (> 150 °C)rangeS02 °F (> 150 °C)Flash point104.0 °F (40.0 °C) Tag Closed CupEvaporation rate> 0.1 BuAcFlammability (solid, gas)Not available.Upper/lower flammability or expusive limitsFlammability limit - lower0.7 %(%)0.7 %f Rammability limit - upper (%)Not available.Vapor pressure< 5 mm Hg @ 20°CVapor density> 10 available.Vapor density> 10 available.Solubility(water)< 15 %Partition coefficient (n-octanol/water)Not establishedAuto-ignition temperature> 392 °F (> 200 °C)Decomposition temperature> 392 °F (> 200 °C)Heat of combustion> 30 kJ/gPercent volatile100 %Specific gravity> 30 kJ/gPercent volatile0.82 - 0.86 @ 20°CVOC (Weight %)97.2 % per U.S. State and Federal Consumer Product Regulations	Physical state	Gas.
OdorOrangeOdor thresholdNot establishedpHNot applicableMetting point/reezing pointNot establishedInitial bolling point and bolling>30 °F (> 150 °C)range>30 °F (> 150 °C)Flash point104.0 °F (40.0 °C) Tag Closed CupEvaporation rate> 0.1 BuAcFlammability colid, gas)Not available.Upper/lower flammability ore0.7 °Cr(%)0.7 °CFlammability limit - lower0.7 °Cr(%)Not available.Explosive limit - lower (%)Not available.fearmability limit - upper (%)Not available.fearmability limit - upper (%)Not available.fearmability limit - upper (%)Not available.for pressure< 5 mm Hg @ 20°CVapor pressure< 5 mm Hg @ 20°CVapor density> 1 (air = 1)Relative density< 15 %Partition coefficient< 392 °F (> 200 °C)Incodeficient< 392 °F (> 200 °C)Partition coefficient> 392 °F (> 200 °C)Incodeficient< 392 °F (> 200 °C)Partition coefficient< 392 °F (> 200 °C)Incodeficient> 392 °F (> 200 °C)Incodeficient< 30 sti @ 25°CPartition coefficient< 30 sti @ 25°CIncodeficient< 30 sti @ 25°CInternorotion< 30 sti @ 25°C <th>Form</th> <th>Aerosol.</th>	Form	Aerosol.
Odor thresholdNot establishedpHNot applicableMelting point/freezing pointNot establishedInitial boiling point and boiling range> 302 °F (> 150 °C)Flash point104.0 °F (40.0 °C) Tag Closed CupEvaporation rate> 0.1 BuAcFlammability (solid, gas)Not available.Upper/lower flammability or expusive limitsFlammability limit - upper (%)flammability limit - upper (%)Not available.Vapor pressure6 %(%)Not available.Vapor pressure< 5 mm Hg @ 20°C	Color	Clear, Off-white.
pHNot applicableMelting point/freezing pointNot establishedInitial boiling point and boiling range> 302 °F (> 150 °C)Flash point104.0 °F (40.0 °C) Tag Closed CupEvaporation rate Evaporation rate> 0.1 BuAcFlammability (solid, gas)Not available.Upper/lower flammability or explustive limits0.7 %Flammability limit - lower (%)0.7 %Flammability limit - lower (%)Not available.Explosive limit - lower (%)Not available.Explosive limit - lower (%)Not available.Explosive limit - upper (%)Not available.Vapor pressure< 5 mm Hg @ 20°CVapor density> 1 (air = 1)Relative densityNot available.Solubility (water)< 15 %Partition coefficient (noctanol/water)Not establishedViscosity< 302 °F (> 200 °C)Decomposition temperature Heat of combustion> 308 u/gPercent volatile100 %Specific gravity.032 @ 2°CVOC (Weight %)97.2 % per U.S. State and Federal Consumer Product Regulations	Odor	Orange
Melting point/freezing pointNot establishedInitial boiling point and boiling range> 302 °F (> 150 °C)Flash point104.0 °F (40.0 °C) Tag Closed CupEvaporation rate> 0.1 BuAcFlammability (solid, gas)Not available.Upper/lower flammability or expusive limits0.7 %flammability limit - lower (%)0.7 %flammability limit - upper (%)6 %flammability limit - upper (%)Not available.flammability limit - upper (%)Not available.Vapor pressure< 5 mm Hg @ 20°CVapor density> 1 (air = 1)Relative densityNot available.Solubility(ies)< 15 %Solubility (water)< 15 %Partition coefficient (n-octanol/water)Not establishedViscosity< 30 scl @ 25°COther information< 30 kJ/gHeat of combustion> 30 kJ/gPercent volatile100 %Specific gravity0.82 - 0.86 @ 20°CVOC (Weight %)97.2 % per U.S. State and Federal Consumer Product Regulations	Odor threshold	Not established
Initial boiling point and boiling range> 302 °F (> 150 °C)Flash point104.0 °F (40.0 °C) Tag Closed CupEvaporation rate> 0.1 BuAcFlammability (solid, gas)Not available.Upper/lower flammability or explosive limits	рН	Not applicable
range       104.0 °F (40.0 °C) Tag Closed Cup         Evaporation rate       > 0.1 BuAc         Flammability (solid, gas)       Not available.         Upper/lower flammability or explosive limits       Flammability limit - lower         Flammability limit - upper       0.7 %         (%)       6 %         Flammability limit - upper       6 %         (%)       Not available.         Explosive limit - lower (%)       Not available.         Explosive limit - lower (%)       Not available.         Vapor pressure       < 5 mm Hg @ 20°C         Vapor density       > 1 (air = 1)         Relative density       Not available.         Solubility(water)       < 15 %         Partition coefficient (n-octanol/water)       Not established         Auto-ignition temperature       > 392 °F (> 200 °C)         Decomposition temperature       > 392 °F (> 200 °C)         Decomposition temperature       > 392 °F (> 200 °C)         Viscosity       < 3 cSt @ 25°C         Other information       > 30 kJ/g         Percent volatile       100 %         Specific gravity       0.82 - 0.86 @ 20°C         VOC (Weight %)       97.2 % per U.S. State and Federal Consumer Product Regulations	Melting point/freezing point	Not established
Evaporation rate> 0.1 BuAcFlammability (solid, gas)Not available.Upper/lower flammability or expussive limitsFlammability limit - lower0.7 %(%)Flammability limit - upper6 %Flammability limit - lower (%)Not available.Explosive limit - lower (%)Not available.Explosive limit - upper (%)Not available.Vapor pressure< 5 mm Hg @ 20°C	•••••••	> 302 °F (> 150 °C)
FlarNot available.Upper/lower flammability or expise limitsFlammability limit - lower0.7 %(%)6 %Flammability limit - upper6 %(%)Not available.Explosive limit - lower (%)Not available.Explosive limit - upper (%)Not available.Vapor pressure< 5 mm Hg @ 20°CVapor density> 1 (air = 1)Relative densityNot available.Solubility (water)< 15 %Partition coefficient (n-ocefficient (n-ocefficient formation)Not establishedViscosity< 392 °F (> 200 °C)Decomposition temperature> 392 °F (> 200 °C)Other information< 3 cst @ 25°CPartet of combustion> 30 kJ/gHeat of combustion> 30 kJ/gPercent volatile100 %Specific gravity0.82 - 0.86 @ 20°CVOC (Weight %)97.2 % per U.S. State and Federal Consumer Product Regulations	Flash point	104.0 °F (40.0 °C) Tag Closed Cup
Upper/lower flammability or explosive limitsFlammability limit - lower0.7 %(%)6 %Flammability limit - upper6 %(%)Not available.Explosive limit - lower (%)Not available.Explosive limit - upper (%)Not available.Vapor pressure<5 mm Hg @ 20°CVapor density> 1 (air = 1)Relative densityNot available.Solubility(ies)<15 %Solubility(water)<15 %Partition coefficient (n-octanol/water)Not establishedViscosity< 392 °F (> 200 °C)Decomposition temperature Viscosity>392 °CVate of combustion<30 kJ/gPercent volatile Specific gravity100 %Specific gravity0.82 - 0.86 @ 20°CVOC (Weight %)97.2 % per U.S. State and Federal Consumer Product Regulations	Evaporation rate	> 0.1 BuAc
Flammability limit - lower (%)0.7 %Flammability limit - upper (%)6 %Explosive limit - lower (%)Not available.Explosive limit - upper (%)Not available.Vapor pressure< 5 mm Hg @ 20°C	Flammability (solid, gas)	Not available.
(%)Flammability limit - upper (%)6 %Flammability limit - lower (%)Not available.Explosive limit - upper (%)Not available.Vapor pressure< 5 mm Hg @ 20°CVapor density> 1 (air = 1)Relative densityNot available.Solubility(ies)Solubility(water)< 15 %Partition coefficient (n-octanol/water)Not establishedViscosity< 392 °F (> 200 °C)Decomposition temperature Viscosity> 392 °F (> 200 °C)Deter information Heat of combustion> 30 kJ/gPercent volatile Specific gravity VOC (Weight %)0.82 - 0.86 @ 20°CVOC (Weight %)97.2 % per U.S. State and Federal Consumer Product Regulations	Upper/lower flammability or exp	losive limits
<ul> <li>(%)</li> <li>Explosive limit - lower (%) Not available.</li> <li>Explosive limit - upper (%) Not available.</li> <li>Vapor pressure &lt; 5 mm Hg @ 20°C</li> <li>Vapor density &gt; 1 (air = 1)</li> <li>Relative density Not available.</li> <li>Solubility(ies) Solubility (water) &lt; 15 %</li> <li>Partition coefficient (n-octanol/water)</li> <li>Auto-ignition temperature &gt; 392 °F (&gt; 200 °C)</li> <li>Decomposition temperature Not established</li> <li>Viscosity &lt; 3 cSt @ 25°C</li> <li>Other information</li> <li>Heat of combustion &gt; 30 kJ/g</li> <li>Percent volatile 100 %</li> <li>Specific gravity 0.82 - 0.86 @ 20°C</li> <li>VOC (Weight %) 97.2 % per U.S. State and Federal Consumer Product Regulations</li> </ul>		0.7 %
Explosive limit - upper (%)Not available.Vapor pressure< 5 mm Hg @ 20°C		6 %
Vapor pressure< 5 mm Hg @ 20°CVapor density> 1 (air = 1)Relative densityNot available.Solubility(ies)< 15 %Solubility (water)< 15 %Partition coefficient (n-octanol/water)Not establishedAuto-ignition temperature (recomposition temperature> 392 °F (> 200 °C)Decomposition temperature ViscosityNot establishedViscosity< 3 cSt @ 25°COther information Heat of combustion Percent volatile100 %Specific gravity VOC (Weight %)97.2 % per U.S. State and Federal Consumer Product Regulations	Explosive limit - lower (%)	Not available.
Vapor density> 1 (air = 1)Relative densityNot available.Solubility(ies)< 15 %Solubility (water)< 15 %Partition coefficient (n-octanol/water)Not establishedAuto-ignition temperature (pecomposition temperature> 392 °F (> 200 °C)Decomposition temperature Viscosity< 3 cSt @ 25°COther information Heat of combustion Specific gravity> 30 kJ/gPercent volatile Specific gravity100 %Specific gravity VOC (Weight %)97.2 % per U.S. State and Federal Consumer Product Regulations	Explosive limit - upper (%)	Not available.
Relative densityNot available.Solubility(ies)Not available.Solubility (water)<15 %	Vapor pressure	< 5 mm Hg @ 20°C
Solubility(ies)< 15 %	Vapor density	> 1 (air = 1)
Solubility (water)< 15 %	Relative density	Not available.
Partition coefficient (n-octanol/water)Not establishedAuto-ignition temperature> 392 °F (> 200 °C)Decomposition temperatureNot establishedViscosity< 3 cSt @ 25°C	Solubility(ies)	
(n-octanol/water)Auto-ignition temperature> 392 °F (> 200 °C)Decomposition temperatureNot establishedViscosity< 3 cSt @ 25°COther information> 30 kJ/gHeat of combustion> 30 kJ/gPercent volatile100 %Specific gravity0.82 - 0.86 @ 20°CVOC (Weight %)97.2 % per U.S. State and Federal Consumer Product Regulations	Solubility (water)	< 15 %
Decomposition temperatureNot establishedViscosity< 3 cSt @ 25°C		Not established
Viscosity       < 3 cSt @ 25°C         Other information          Heat of combustion       > 30 kJ/g         Percent volatile       100 %         Specific gravity       0.82 - 0.86 @ 20°C         VOC (Weight %)       97.2 % per U.S. State and Federal Consumer Product Regulations	Auto-ignition temperature	> 392 °F (> 200 °C)
Other information         Heat of combustion       > 30 kJ/g         Percent volatile       100 %         Specific gravity       0.82 - 0.86 @ 20°C         VOC (Weight %)       97.2 % per U.S. State and Federal Consumer Product Regulations	Decomposition temperature	Not established
Heat of combustion> 30 kJ/gPercent volatile100 %Specific gravity0.82 - 0.86 @ 20°CVOC (Weight %)97.2 % per U.S. State and Federal Consumer Product Regulations	Viscosity	< 3 cSt @ 25°C
Percent volatile100 %Specific gravity0.82 - 0.86 @ 20°CVOC (Weight %)97.2 % per U.S. State and Federal Consumer Product Regulations	Other information	
Specific gravity0.82 - 0.86 @ 20°CVOC (Weight %)97.2 % per U.S. State and Federal Consumer Product Regulations	Heat of combustion	> 30 kJ/g
VOC (Weight %) 97.2 % per U.S. State and Federal Consumer Product Regulations	Percent volatile	100 %
	Specific gravity	0.82 - 0.86 @ 20°C
	VOC (Weight %)	

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

## 11. Toxicological information

## Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system.
Skin contact	Causes skin irritation. May cause sensitization by skin contact.
Eye contact	Causes eye irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms related to the physical, chemical and toxicological characteristics	Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

### Information on toxicological effects

Acute toxicity	Based on available data, the classification criteria are not met.		
Components	Species Test Results		
3-Methoxy-3-methyl-1-butanol (M	MB) (CAS 56539-66-3)		
Acute			
Dermal			
LD50	Rat	> 2000 mg/kg, 24 Hours	
Distillates Petroleum Hydrotreate	d Light (CAS 64742-47-8)		
Acute			
<i>Dermal</i> LD50	Rabbit	> 2000 mg/kg	
ED30	habbit	> 2000 mg/kg, 24 Hours	
Inholotion		> 2000 Hig/kg, 24 Hours	
Inhalation LC50	Cat	> 6.4 mg/l, 6 Hours	
2000	Bat	> 7.5 mg/l, 6 Hours	
	Trat	> 4.3 mg/l, 4 Hours	
		> 0.1 mg/l, 8 Hours	
<i>Oral</i> LD50	Rat	> 5000 mg/kg	
d-limonene (CAS 5989-27-5)	Trat	> 3000 mg/kg	
Acute			
Oral			
LD50	Mouse	5600 - 6600 mg/kg	
	Rat	> 2000 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye	Causes serious eye irritation.		
irritation			
Respiratory or skin sensitizatio	n		
Respiratory sensitization	Based on available data, the classification criteria are not met.		
Skin sensitization	May cause sensitization by skin contact.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	Based on available data, the classification criteria	are not met.	
	Evaluation of Carcinogenicity		
d-limonene (CAS 5989-2 OSHA Specifically Regulate Not listed.	27-5) 3 Not classifiable a ed Substances (29 CFR 1910.1001-1050)	s to carcinogenicity to humans.	

Reproductive toxicity	Based on available data, the classification criteria are not met.
Specific target organ toxicity - single exposure	Based on available data, the classification criteria are not met.
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	Prolonged exposure may cause chronic effects.

## **12. Ecological information** Ecotoxicity

Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
Distillates Petroleum Hydrot	reated Light	CAS 64742-47-8)	
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
d-limonene (CAS 5989-27-5	i)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	69.6 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	0.619 - 0.796 mg/l, 96 hours
ersistence and degradability	Not inher	ently biodegradable.	
ioaccumulative potential	No data available.		
Partition coefficient n-octa	anol / water (	log Kow)	
d-limonene		4.232	
obility in soil	Readily absorbed into soil.		
ther adverse effects	None known.		
3. Disposal consideration	ons		
isposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into		

	and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F D003: Waste Reactive material
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

-	
DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No
Special precautions for user	· Not available.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

#### ΙΑΤΑ

IATA	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
Special precautions for user	Not available.
Other information	
Passenger and cargo	Allowed.
aircraft	
Cargo aircraft only	Allowed.
IMDG	
LINE CONTRACTOR	
UN number	UN1950
UN number UN proper shipping name	Aerosols, flammable
UN proper shipping name	
UN proper shipping name Transport hazard class(es)	Aerosols, flammable
UN proper shipping name Transport hazard class(es) Class	Aerosols, flammable
UN proper shipping name Transport hazard class(es) Class Subsidiary risk	Aerosols, flammable 2.1
UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s)	Aerosols, flammable 2.1 - 2.1
UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group	Aerosols, flammable 2.1 - 2.1
UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Environmental hazards	Aerosols, flammable 2.1 - 2.1 Not applicable.
UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Environmental hazards Marine pollutant	Aerosols, flammable 2.1 - 2.1 Not applicable. Yes F-D, S-U
UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Environmental hazards Marine pollutant EmS Special precautions for user Transport in bulk according to	Aerosols, flammable 2.1 - 2.1 Not applicable. Yes F-D, S-U
UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Environmental hazards Marine pollutant EmS Special precautions for user	Aerosols, flammable 2.1 - 2.1 Not applicable. Yes F-D, S-U Not available.
UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Environmental hazards Marine pollutant EmS Special precautions for user Transport in bulk according to	Aerosols, flammable 2.1 - 2.1 Not applicable. Yes F-D, S-U Not available.



#### Marine pollutant



#### 15. Regulatory information

#### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Hazard categories

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No chemical

## SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated. (SDWA)

#### US state regulations

- US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.
- US. Massachusetts RTK Substance List Carbon Dioxide (CAS 124-38-9)
- US. New Jersey Worker and Community Right-to-Know Act

Carbon Dioxide (CAS 124-38-9)

- US. Pennsylvania Worker and Community Right-to-Know Law
  - Carbon Dioxide (CAS 124-38-9)

US. Rhode Island RTK

Not regulated.

#### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Supersedes:	4 May 2009
Date Revised:	7 August 2015
Disclaimer	The information contained herein is provided in good faith and is believed to be correct as of the date hereof. However, Obtura Spartan makes no recommendation as to the comprehensiveness or accuracy of the information. It is expected that individuals receiving the information will exercise their independent judgment in determining its appropriateness for particular purpose.
	NO REPRESENTATIONS, OR WARRANTIES, EITHER EXPRESSED OR IMPLIED OF MERCHANTABILITY,

NO REPRESENTATIONS, OR WARRANTIES, EITHER EXPRESSED OR IMPLIED OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR TO THE PRODUCT TO WHICH THE INFORMATION REFERS.