

Printing date 14.12.2015 Revision: 14.12.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: 782150 Giroform Die Link silber

1.2 Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

Application of the substance / the preparation: Auxiliary for dental technology

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Firmenbezeichnung Amann Girrbach AG Herrschaftswiesen 1 A-6842 Koblach

Telefon: 0043 5523 623330 Fax: 0043 5523 55990

Email: austria@amanngirrbach.com Internet: www.amanngirrbach.com

Inverkehrbringer Amann Girrbach GmbH Duerrenweg 40 D-75177 Pforzheim

Telefon: 0049 7231 957100 Fax: 0049 7231 957129

Email: germany@amanngirrbach.com Internet: www.amanngirrbach.com

Further information obtainable from: Amann Girrbach GmbH

1.4 Emergency telephone number:

Giftinformationszentrum-Nord / GIZ-Nord Poisons Centre

Telefon / Phone +49 (0) 551/19240

24h / 7d

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture:

Classification according to Regulation (EC) No 1272/2008:



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements:

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 14.12.2015 Revision: 14.12.2015

Trade name: 782150 Giroform Die Link silber

(Contd. of page 1)

Hazard pictograms:





GHS02 GHS07

Signal word: Danger

Hazard-determining components of labelling:

ethyl acetate n-butyl acetate

Hazard statements:

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards:

Results of PBT and vPvB assessment:

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

Dangerous components.	
CAS: 141-78-6 ethyl acetate	25-50%
EINECS: 205-500-4 🚸 Flam. Liq. 2, H225; 🕚 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 123-86-4 n-butyl acetate	10-<25%
EINECS: 204-658-1 🚸 Flam. Liq. 3, H226; 🕔 STOT SE 3, H336	
CAS: 67-63-0 propan-2-ol	2.5-<10%
EINECS: 200-661-7 🚸 Flam. Liq. 2, H225; 🕔 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 108-65-6 2-methoxy-1-methylethyl acetate	0.1-≤2.5%
EINECS: 203-603-9 🊸 Flam. Liq. 3, H226	
Additional information: For the wording of the listed risk phrases refer to section 16.	

(Contd. on page 3)



Printing date 14.12.2015 Revision: 14.12.2015

Trade name: 782150 Giroform Die Link silber

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures:

General information:

Take affected persons out into the fresh air. Do not leave affected persons unattended.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

After swallowing: Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed:

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media:

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture:

Formation of toxic gases is possible during heating or in case of fire.

Can form explosive gas-air mixtures.

5.3 Advice for firefighters:

Protective equipment: Do not inhale explosion gases or combustion gases.

Additional information:

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Open and handle receptacle with care.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

(Contd. on page 4)



Printing date 14.12.2015 Revision: 14.12.2015

Trade name: 782150 Giroform Die Link silber

(Contd. of page 3)

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Highly volatile, flammable constituents are released during processing.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities:

Storage:

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in a cool location.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters:

Ingredients with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

WEL Short-term value: 400 ppm Long-term value: 200 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

8.2 Exposure controls:

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection: Not necessary if room is well-ventilated.

Protection of hands: Protective gloves

Material of gloves:

Nitrile rubber, NBR

Butyl rubber, BR

Natural rubber, NR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

(Contd. on page 5)



Printing date 14.12.2015 Revision: 14.12.2015

Trade name: 782150 Giroform Die Link silber

(Contd. of page 4)

checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to

be observed.

Eye protection: Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

General Information:

Appearance:

Form: Fluid

Colour: Different according to colouring

Odour: Characteristic
Odour threshold: Not determined.

pH-value: Not determined.

Change in condition:

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 77 °C Flash point: -1 °C

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 370 °C

Decomposition temperature: Not determined.

Self-igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower:
Upper:

1.2 Vol %
11.5 Vol %

11.5 Vol %

Vapour pressure at 20 °C:

97 hPa

Density at 20 °C:

Relative density:
Vapour density:
Vapour density:

Evaporation rate:

1.2 Vol %
11.5 Vol %
10.95 g/cm³
Not determined.
Not applicable.

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

9.2 Other information: No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity: No further relevant information available.

10.2 Chemical stability:

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

(Contd. on page 6)



Printing date 14.12.2015 Revision: 14.12.2015

Trade name: 782150 Giroform Die Link silber

(Contd. of page 5)

10.3 Possibility of hazardous reactions: Forms explosive gas mixture with air.

10.4 Conditions to avoid: No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

Flammable gases/vapours

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

Acute toxicity Based on available data, the classification criteria are not met.

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity:

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability: No further relevant information available.

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment:

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects: No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods:

Recommendation:

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue:

Dispose of contents/container in accordance with local/regional/national/international regulations.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

(Contd. on page 7)



Printing date 14.12.2015 Revision: 14.12.2015

Trade name: 782150 Giroform Die Link silber

(Contd. of page 6)

SECTION 14: Transport information

14.1 UN-Number:

ADR, IMDG, IATA UN1263

14.2 UN proper shipping name:

ADR 1263 PAINT
IMDG PAINT
IATA Paint
14.3 Transport hazard class(es):

ADR, IMDG, IATA



Class: 3 Flammable liquids.

Label: 3

14.4 Packing group:

ADR, IMDG, IATA

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user: Warning: Flammable liquids.

Danger code (Kemler): 33
EMS Number: F-E,S-E

14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ): 5L
Transport category: 2
Tunnel restriction code: D/E

UN "Model Regulation": UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

(Contd. on page 8)



Printing date 14.12.2015 Revision: 14.12.2015

Trade name: 782150 Giroform Die Link silber

(Contd. of page 7)

Department issuing SDS:

ADEEGO GmbH Wildsteig 4A D-42113 Wuppertal Tel. +49 (0) 202 2575700 Fax. +49 (0) 202 2575701

Email: mail@adeego.de

www.adeego.de

Contact: Dr. Axel Deeg

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3